



ICAL International Customs And Logistics
 47 Lambeck Drive, Tullamarine
 Victoria, 3043 Australia
 Telephone: (03) 9335 2566
 Fax: (03) 9335 2890
 Mobile: 0413 99 33 44
 Email: mark@ical.com.au
 www.ical.com.au www.plasticpallets.com.au

20 FOOT REEFER CONTAINERS (6M)				Minimum	Maximum
Internal Dimensions*	Length	Meters		5.340	5.479
	Width	Meters		2.200	2.286
	Height#	Meters		2.225	2.257
Door Openings*	Width	Meters		2.200	2.286
	Height	Meters		2.180	2.220
Load Capacity*			M3	26.14	28.27
Container Weight*			Kg	2,870	3380
Maximum Payload*			Kg	20,620	24,060

40 FOOT REEFER CONTAINERS (12M)				Minimum	Maximum
Internal Dimensions*	Length	Meters		11.207	11.550
	Width	Meters		2.246	2.250
	Height#	Meters		2.183	2.215
Door Openings*	Width	Meters		2.216	2.250
	Height	Meters		2.118	2.160
Load Capacity *			M3	54.95	57.56
Container Weight*			Kg	4.535	4.840
Maximum Payload*			Kg	25,640	27,965

40 FOOT REEFER CONTAINERS (12M)				Minimum	Maximum
Internal Dimensions*	Length	Meters		11.207	11.550
	Width	Meters		2.246	2.250
	Height#	Meters		2.507	2.553
Door Openings*	Width	Meters		2.216	2.250
	Height	Meters		2.457	2.501
Load Capacity *			M3	63.10	66.34
Container Weight*			Kg	4.535	4.840
Maximum Payload*			Kg	25,500	27,100

* Tolerance factors must always be taken into account by the shipper.
 # Leave at least a 10cm gap between the roof and your cargo for air flow.
 3 Phase power (32 amp) is required to operate the refrigerated container, which is fitted with CEE form plugs. This documents is only to be used as a guide only

Best regards,

Mark Coleman
 Seafreight Manager.

All Business is undertaken subject to our standard terms and conditions of trading, available upon request.